REQUEST FOR COMMITTEE ACTION

HENDERSON COUNTY

TECHNICAL REVIEW COMMITEE

MEETING: January 21, 2014

SUBJECT: Major Site Plan Review Waffle House

PRESENTER: Toby Linville

ATTACHMENTS: Staff Report

SUMMARY OF REQUEST: Major site plan review-Retail Sales and Service-Waffle House

SUGGESTED MOTION: I move that the TRC approve the major site plan for Waffle House



Henderson County, North Carolina Code Enforcement Services

1. Committee Request

- 1.1. Applicant: Waffle House
- 1.2. Request: Major Site Plan Approval
- 1.3. **PIN:** 9651492507
- 1.4. Size: .844 acres +/-
- 1.5. Location: The subject area is located on Asheville Hwy just north of I-26.
- 1.6. Supplemental Requirements:

SR 7.14. Retail Sales and Services Less than or Equal to 50,000 Square Feet (Gross Floor Area)

(1) Site Plan. Major *Site Plan* required in accordance with §200A-331 (Major Site Plan Review).
 (2) Lighting. *Adequate lighting* shall be placed in areas used for vehicular/pedestrian access including, but not limited to: stairs, sidewalks, crosswalks, intersections, or changes in grade. *Lighting mitigation* required.




Waffle House Retail Sales and Service Staff Report

2. <u>Current Conditions</u>

2.1 Current Use: This parcel is currently in vacant.


2.2 Adjacent Area Uses: The surrounding properties consist of mixed commercial uses.

2.3 Zoning: The surrounding property to the north, east, west and south is zoned Regional Commercial (RC).





- **3.** <u>Floodplain /Watershed Protection</u> The property is not located in a Special Flood Hazard Area. The property is not in a Water Supply Watershed district.
- Water and Sewer This property will be served by public water and sewer.
 Public Water: City of Hendersonville Water
 Public Sewer: Cane Creek Sewer



Map C: CCP Future Land Use Map

5. <u>Comprehensive Plan</u>

The 2020 CCP: The CCP Future Land Use Map places the Subject Area in the Community Service Center Area. The text and map of the 2020 CCP suggest that the Subject Area would be more suitable for the following:

 Community Service Centers are intended to be intensive, efficient, defined concentrations of mixed services that meet the needs of the surrounding community and defined service areas. Community Service Centers are appropriate for a mixture of commercial uses scaled to the service area in question; residential uses of varying densities depending upon available services; and Community Facilities such as schools, parks, community centers, and other similar Community Facilities. The mixture and intensity of land uses contained within Community Service Centers are intended to be appropriate within the context of the surrounding community and intended service area. Community Service Centers should also be properly controlled by appropriate aesthetic standards, access management standards, and other appropriate development control measures.

6. <u>Staff Recommendations</u>

6.1Staff's Position at this time, under the guidelines of current plans, policies and studies, is to approve the Major Site Plan because it is consistent with the current surrounding land uses and future land use recommendations.

Waffle House Retail Sales and Service Staff Report

7. <u>Photographs</u>

Looking NE into property



Looking SW (Auto Advantage/Hardees)




Waffle House Retail Sales and Service Staff Report




Looking South (Hardees/I-26)

Looking E into property







 \subset


• •


Ù


 \leq


AY


 \mathcal{N}











GRAPHIC SCALE 1" = 20'

PROJECT NAME: WAFFLE HOUSE UNIT #____ US HIGHWAY 25 HOOPERS CREEK TOWNSHIP HENDERSON COUNTY NORTH CAROLINA SHEET TITLE: GRADING, STORM DRAINAGE, AND EROSION CONTROL

S

 \supset


 \bigcirc


A

 \geq

PLAN PROJECT No. SHEET No. WAFXXX C - 4XX/XX/XX | of 8

ISSUE NO. 1





DATE

ΧΧ/ΧΧ/ΧΧ

ISSUE NO. 1

of 8

GRAPHIC SCALE

1" = 20'

SEEDING SPECIFICATIONS

- 1 TEMPORARY COVER
- A. LIME APPLY AT THE RATE REQUIRED BY THE SOIL TEST RECOMMENDATIONS. IF NO SOIL TEST IS PERFORMED, THEN APPLY AT A RATE OF 2,000 LBS PER ACRE.
- B. FERTILIZER APPLY AT THE RATE REQUIRED BY THE SOIL TEST RECOMMENDATIONS. IF NO SOIL TEST IS PERFORMED, THEN APPLY 10-10-10 GRADE FERTILIZER AT A RATE OF 750 LBS PER ACRE. FOR LATE WINTER/EARLY SPRING & SUMMER SEED MIX AND 1000 LBS PER ACRE FOR FALL SEED MIX.
- BOTH LIME AND FERTILIZER SHALL BE INCORPORATED UNIFORMLY INTO THE TOP 4-6 INCHES OF SOIL. IF A HYDRAULIC SEEDER IS USED, DO NOT MIX SEED AND FERTILIZER MORE THAN 30 MINUTES BEFORE APPLICATION.
- SEEDING CONTRACTOR SHALL SELECT A QUICK GROWING GRASS WITH HIGH SEEDING VIGOR THAT IS SUITED TO THE AREA, TIME OF PLANTING AND THAT WILL NOT INTERFERE WITH PLANTS TO BE SOWN LATER FOR PERMANENT COVER. EVENLY APPLY SEED USING A BROADCAST SEEDER, DRILL, CULTIPACKER SEEDER OR HYDROSEEDER.
- BROADCAST SEEDING AND HYDRO-SEEDING ARE APPROPRIATE FOR STEEP SLOPES WHERE EQUIPMENT CAN NOT BE DRIVEN. HAND BROADCASTING IS NOT ALLOWED BECAUSE OF THE DIFFICULTY IN ACHIEVING AN UNIFORM DISTRIBUTION.
- LATE WINTER/ENTRY SPRING SEED MIX:
- ABOVE 2,500 FT: FEB. 15 MAY 15 BELOW 2,500 FT: FEB. 1 - MAY 1
- RYE (GRAIN) 120 LB/AC. ANNUAL LESPEDEZA (KOREAN) – 50 LB/AC.
- OMIT ANNUAL LESPEDEZA (KOREAN) WHEN DURATION OF TEMPORARY COVER IS NOT EXTENDED BEYOND JUNE.
- SUMMER SEED MIX: ABOVE 2,500 FT: MAY 15 - AUG 15 BELOW 2,500 FT: MAY 1 - AUG 15
- GERMAN MILLET 40 LB/AC
- FALL SEED MIX: AUG 15 - DEC 15
- RYE (GRAIN) 120 LB/AC
- IF PERMANENT SEEDING IS NOT INSTALLED OVER FALL SEED MIX BY MARCH 1st, THEN TOP DRESS WITH 50 LB/AC OF NITROGEN.
- IF IT IS NECESSARY TO EXTEND TEMPORARY COVER BEYOND JUNE 15th. OVERSEED WITH 50 LB/AC OF KOREAN LESPEDEZA IN LATE FEBRUARY OR EARLY MARCH.
- ALL SEEDS SHALL HAVE BEEN TESTED NOT MORE THAN 6 MONTHS PRIOR TO THE DATE OF SEEDING. ENGINEER MAY REQUIRE PROOF OF TESTING AND RESULTS.
- D. MULCHING IN ORDER TO REDUCE DAMAGE FROM WATER RUNOFF AND IMPROVE MOISTURE CONDITIONS FOR SEEDLINGS, A MULCH MATERIAL SHALL BE FURNISHED WHEN TEMPORARY SEEDING IS DONE.
 - ACCEPTABLE MATERIALS ARE:
 - 1. DRY, UNCHOPPED, UNWEATHERED WHEAT OR OAT STRAW FREE OF SEEDS OF COMPETING PLANTS. AT A RATE OF 4,000 LBS PER ACRE. ANCHOR STRAW BY TACKING WITH ASPHALT, NETTING OR A MULCH ANCHORING TOOL. A DISK WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS A MULCH ANCHORING TOOL.
 - 2. WOOD FIBER (CELLULOSE) MAY BE HYDROSEEDED AT A RATE OF /50 LBS/AC. DO NOT USE IN HOT, DRY WEATHER
 - 3. JUTE MATTING
 - A SLURRY MIXTURE OF WATER, FERTILIZER, SEED AND CELLULOSE FIBER MULCH IS ACCEPTABLE ON THIS PROJECT.
- II PERMANENT COVER
- A. LIME APPLY AT THE RATE REQUIRED BY THE SOIL TEST RECOMMENDATIONS. IF NO SOIL TEST IS PERFORMED, THEN APPLY GROUND AGRICULTURAL LIME AT A RATE OF 75 LB/1000 S.F.
- FERTILIZER APPLY AT THE RATE REQUIRED BY THE SOIL TEST RECOMMENDATIONS. IF NO SOIL TEST IS PERFORMED. THEN APPLY 5-10-10 AT A RATE OF 40 LBS/AC.
- BOTH LIME & FERTILIZER SHALL BE INCORPORATED UNIFORMLY INTO THE TOP 4 INCHES OF SOIL.
- C. SEEDING -NURSE CROP -GERMAN MILLET (SETARIA ITALICA) AT A RATE OF 10 LB/AC BETWEEN MAY 11 TO SEPT 30.
- PRIMARY CROP -KENTUCKY 31 TALL FESCUE (SCHEDONORUS PHOENIX) AT A RATE OF 100 LB/AC BETWEEN AUG 15 TO MAY 1ST.
- MULCHING IN ORDER TO REDUCE DAMAGE FROM WATER RUNOFF AND D. IMPROVE MOISTURE CONDITIONS FOR SEEDLINGS, A MULCH MATERIAL SHALL BE FURNISHED WHEN PERMANENT SEEDING IS DONE. ACCEPTABLE MATERIALS ARE:
- 1. DRY, UNCHOPPED, UNWEATHERED WHEAT OR OAT STRAW FREE OF SEEDS OF COMPETING PLANTS. AT A RATE OF 4.000 LBS PER ACRE.
- ANCHOR STRAW BY TACKING WITH ASPHALT, NETTING OR A MULCH ANCHORING TOOL. A DISK WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS A MULCH ANCHORING TOOL.
- 2. WOOD FIBER (CELLULOSE) MAY BE HYDROSEEDED AT A RATE OF 750 LBS/AC. DO NOT USE IN HOT, DRY WEATHER.
- 3. JUTE MATTING
- A SLURRY MIXTURE OF WATER, FERTILIZER, SEED AND CELLULOSE FIBER MULCH IS ACCEPTABLE ON THIS PROJECT.
- ADD NETTING TO STEEP SLOPES AND STAPLE PER MANUFACTURERS RECOMMENDATIONS WHEN SHOWN ON PLANS.

GENERAL CONSTRUCTION NOTES

- . All work and construction activities on the project site shall comply with all applicable OSHA regulations and requirements. It is the Contractor's responsibility to maintain a safe work site.
- 2. The Engineer and Owner reserve the right to modify project work items (including grading) as deemed necessary for the successful completion of the project. The Contractor may suggest adjustments to grading or other work items to be approved by the Engineer or Owner.
- 3. The Contractor shall comply with the Geotechnical Report for the placement of fill and compaction requirements. If no report is available, the following minimum standards shall apply:


Placement of fill:


- A. Place the material in successive horizontal layers not exceeding 8" for the full width of the cross section.
- B. Fill shall be placed only when it is within 3% of its optimum moisture content as determined by a Standard Proctor ASTM D 698.
- C. Each layer of fill shall be spread evenly and shall be compacted to its specified density as determined by Standard Proctor ASTM D 698 before new layers are placed and compacted.
- D. Sloped ground surfaces steeper than one vertical to four horizontal, on which fill is to be placed, shall be stepped or benched such that fill material will bond to the existing surfaces.
- E. Embankment slopes shall be constructed by filling one (1) foot beyond the proposed finished slope surface for each lift. Compaction equipment shall work to the edge of each lift. After the entire fill is placed and compacted, the outside foot of the slope shall be trimmed to the design slope with a dozer. Unless indicated on the drawings, no fill slopes shall be steeper than 2 horizontal to 1 vertical.

Compaction:


Proctor

- A. Structural Fill Under Buildings and Within 10' of Building Perimeter: 100% of Standard Proctor the entire depth of fill.
- B. Under Walks, Drives, Pads, and Paved Areas: 95% of Standard Proctor except 100% of Standard Proctor in the upper 2'.
- C. Under Lawns and Planting Areas Beyond 10' from Building: 95% of Standard
- D. Backfill in Trenches: Comply with compaction requirements for the area through which the trench runs.





NOT TO SCALE



5. Disposable Materials:

- A. Clearing and grubbing wastes shall be removed from the site and properly disposed of by the contractor at their expense, unless otherwise specified.
- B. Solid wastes to be removed such as sidewalks, curbs, pavement, etc. may be placed in specified disposal areas if permitted by the appropriate agencies and approved by the Owner. This material shall be spread and mixed with dirt eliminating all voids. This material shall have a minimum cover of 2. The Contractor shall maintain specified compaction requirements in these areas. When disposal sites are not provided, the Contractor shall remove this waste from the site and properly dispose of it at their expense.
- C. Abandoned utilities such as culverts, water pipe, hydrants, casting, pipe appurtenances, utility poles, etc. shall be the property of the specified utility agency or company having jurisdiction. Before the Contractor can remove, destroy, salvage, re-use, sell or store for their own use any abandoned utility, they must present to the owner written permission from the utility involved.
- D. Unless otherwise noted on the plans, burning will not be allowed on this project. Should burning be allowed by the owner, it is the Contractor's responsibility to obtain all necessary permits (at their expense) and follow all applicable rules and regulations.
- 6. Unless otherwise specified, all base, paving, curbing and other concrete work shall conform to the local municipality or NCDOT specifications for construction. All water and sewer construction shall conform to the local utility requirements and/or the NCDENR minimum standards.
- In the event excessive ground water or springs are encountered within the limits of construction, the Contractor shall install necessary underdrains and stone as directed by the Engineer. All work shall be paid based upon the unit prices unless of herwise specified.
- 8. The Contractor is responsible for the coordination of adjustment of all utility surface accesses (including manhole covers, valve boxes, etc.) whether he performs the work or the utility company performs the work.
- 9. The Contractor shall control all "dust" by periodic watering and shall provide access at all times for property owners within the project and for emergency vehicles. All open ditches and hazardous areas shall be clearly marked in accordance with OSHA regulations.
- 10. All areas of exposed soil shall be seeded, fertilized and mulched according to the specifications. The finished surface shall be to grade and smooth, free of all rocks larger than 3", equipment tracks, dirt clods, bumps, ridges, and gouges prior to seeding. The surface shall be loosened to a depth of 1" + /- to accept seed. The Contractor shall not proceed with seeding operations without first obtaining the Engineer's approval of the graded surface. All seeding shall be performed by a mechanical "hydro-seeder". The Engineer prior to seeding must approve hand seeding on any area.

NPDES REQUIREMENTS

The contractor should be aware that any project with a disturbed area of greater than one acre must now comply with NPDES requirements for new construction projects. The contractor should obtain a copy of the plan approval and should follow all requirements including but not limited to: A.) GROUND STABILIZATION

Site Area Description	Stabilization Time Frame	Stabilization Time Exceptions
Perimeter dikes, swales, ditches and slopes	7 Days	None
High Quality Water (HQW) Zones	7 Days	None
Slopes steeper than or = 3:1	7 Days	If Slopes are 10' or length and are not st 2:1, 14 days are o
Slopes flatter than 3:1	14 Days	7 days for slopes gre 50 feet in lend
All other areas with slopes flatter than 4:1	14 Days	None (except for perin HQW Zones)

*"Extensions of time may be approved by the permitting authority base on weather or other site-specific conditions that make compliance impracticable." (Section II.b (2)(B))

1. Placement and upkeep of rain gauge on site that must be monitored throughout the course of the project.

2. The contractor shall keep a log of all rainfall events, erosion control activities, and inspections throughout the course of the project. This log must be kept on site at all times and be available for inspection


3. The contractor shall inspect all erosion control measures in accordance with the NPDES requirements. A minimum inspection schedule of weekly and with in 24 hours after every significant (1/2) inch or more) rainfall event (obtain copy of the permit for this project for details.)


3.) INSPECTONS

1. Inspection reports must be available on-site during business hours unless a site-specific exemption is approved. 2. Records must be kept for 3 years and available upon request.

) BUILDING WASTE HANDLING

1. No paint or liquid wastes in stream or storm drains. 2. Dedicated areas for demolition, construction and other wastes located 50' from storm drains and streams unless no reasonable alternatives are available. 3. Earthen-material stockpiles located 50' from storm drains unless no reasonable alternative available. 4. Concrete materials must be controlled to avoid contact with surface waters, wetlands, or buffers.





F:\USERS\Will\projects\Waffle House - I26\project file\dwa\c-7 utility plan.dwa. 12/18/2013 2:28:4;

